

PRODUCTS: LED CEILING LIGHT



18W RGB DIMMABLE LED CEILING LIGHT

Part No. : IL-CL18-RGB

Power: 18W

Color: RGB (3 in 1)

Working Voltage: DC12V for LED down light, outside power supply AC100V-240V

Size: $\phi 140 \times 54$

Material: Aluminum Alloy

Projection Distance: >5meter

Beam Angle: 38 Degrees

Characteristics:

A. Realize the series connected pattern autocode through the encoder

B. With external controller to achieve RGB dimming independently, and variety of color changing

C. With eternal DMX512 control mode

- Do not touch the surface while the light is on

Applications:

1. Recess lighting, shelf lighting, ceiling/wall coves
2. Cabinet and under counter lighting, office work station
3. Back lighting, step lighting, light boxes
4. Merchandising, exhibition stands and panels



IL-B0101-B(0200 LED)

LIGHT SOURCE: HIGH POWER LED

BEAM ANGLE: 85°

DIAMETER OF THE ROUND PART: 6"

POWER CONSUMPTION: 13W

LUMINOUS FLUX: 640(LM)

INPUT VOLTAGE: 220-240VAC

OPERATING CURRENT: 65MA


RA: >85

PF: >0.9

TRIAC DIMMABLE

MATERIAL: DIECAST ALUMINUM

OPERATING TEMPERATURE: -30°C - +40°C



IL-B0161(6" LED)

LIGHT SOURCE: HIGH POWER LED

BEAM ANGLE: 85°

DIAMETER OF THE ROUND PART: 6"

POWER CONSUMPTION: 12.6W

LUMINOUS FLUX: 620(LM)

INPUT VOLTAGE: 110-120VAC

OPERATING CURRENT: 112MA

BASE: E26

RA: >85

PF: >0.9

TRIAC DIMMABLE

OPERATING TEMPERATURE: -30°C - +40°C

