

DECORATIVE 19" HIGH BAY INDUCTION LIGHTS

APPLICATION, FEATURES AND BENEFITS

- HYBRID - Heat and impact resistant UV protected diffuser and lens with patented Miro (TM) reflector insert.
- Ballast made with long life components
- InstantON(TM) flicker-free Cold Start and Hot Re-Start
- Correlated Color Temperature of 5000 K for greater visibility
- High Power Factor, Low THD - Replaceable Ballast
- Advanced phosphors for high Lumen Maintenance and high lumen output
- Up to 20 years Maintenance free operation





Circular Induction Lamp
Inside



SPECIFICATIONS:

- Ballast Type: Electronic
- Start Method: InstantON
- Hot Re-start: InstantON
- Universal Input Line Voltage: 120-277 VAC
- Input Line Frequency: 50/60 Hz
- Lamp/Ballast System Life: 100,000 Hrs.
- Lumen Maintenance @75,000Hrs: >70%
- Color Temperature: 5000
- Color Rendering Index (CRI): above 83
- Minimum Starting Temperature: -20 F
- Maximum Operating Temperature: 160 F
- Lamp Operating Frequency: 250 kHz
- Power Factor: > 0.98
- Total Harmonic Distortion: < 10%
- Inrush Current Peak: < 10 Amp
- ETL Listed: Yes
- FCC Compliance: Part 18, Subp. C

PRODUCT INFORMATION

Item No.	Description	Watts	Initial Lumens	Line Voltage Supply	Line Current	Total Harmonic Distortion (THD)	Power Factor	Packaging Dimensions		
								Width	Length	Height
ILI-19-HYB	19" High-Bay - Hybrid	40	3,200	120-277 VAC	0.35-0.15 Amp	<10%	0.98	24 in. 610 mm	24 in. 610 mm	30 in. 762 mm
ILI-19-HYB	19" High-Bay - Hybrid	80	6,400	120-277 VAC	0.69-0.30 Amp	<10%	0.98	24 in. 610 mm	24 in. 610 mm	30 in. 762 mm
ILI-19-HYB	19" High-Bay - Hybrid	100	8,000	120-277 VAC	0.87-0.37 Amp	<10%	0.98	24 in. 610 mm	24 in. 610 mm	30 in. 762 mm
ILI-19-HYB	19" High Bay - Hybrid	150	12,000	120-277 VAC	1.31-0.56 Amp	<10%	0.98	24 in. 610 mm	24 in. 610 mm	30 in. 762 mm

Fixture Weight = 20 - 25 lbs.

ORDER INFORMATION

MODEL	WATTAGE	VOLTAGE	OPTIONS	ACCESSORIES	COLOR
IL-19-HYB					
Impact Lighting Inc.	40	UNV = Universal	*C3 - 3' Cord	*LD - Photo Cell	BLK - Black
19" High Bay	80	480 = 480V	PC3 - 3' Cord w/ NEMA plug	MD - Motion Sensor	***Custom
Hybrid	100		**PL - Polycarbonate Lens		
	150				

*Product comes standard with 3' Cord - no plug

** Product comes with polycarbonate lens

*** Custom colors available