

IMPACT INDUCTION LAMPS™ (con't)

HIGH BAY PROFILED ALUMINUM LAMP FIXTURE



1. Vacuum coated inner surface aluminum hood and clear glass cover maximize lumen output
2. Tempered glass cover held by profiled aluminum ring for better appearance and durable use
3. Special thermal design for longer lifespan
4. IP Class: IP65 (If use 3/4" hanging pole with ribbons), IP53 (If use hook)

LAMP AND BALLAST

1. Impact's 80-250W round type induction lamp with high lumen efficiency, high lumen maintenance, long lifespan and excellent CRI
2. Impact's 80-250W electronic ballast with die cast aluminum case features high power factor(>0.96), low energy loss and long lifespan

APPLICATION

Industrial factory, warehouse, stadium, airport, railway station, gas station, supermarket and other indoor locations

SPECIFICATIONS

lamp	wattage (w)	ballast loss(w)	voltage (v)	cct (k)	ambient temperature	Installation	Replace mh lamp(w)
WJY80H850W/T	80	<8					175
WJY100H850W/T	100	<10					250
WJY120H850W/T	120	<12	AC:120-277V	5000	-25 -40 °C	Hook or 3/4" hanging pole	320
WJY150H850W/T	150	<15	AC:208-347V		-13 -104 °F		400
WJY200H850W/T	200	<20					400
WJY250H850W/T	250	<25					600

ORDER INFORMATION

MODEL ILI-PA	WATTS	COLOR TEMP	VOLTAGE	BASE	QUANTITY
Impact Lighting Inc. Profiled Aluminum	80 100 120 150 200 250	5000	120 - 277V 208 - 347V	Hook 0.75" Hanging Pole	



HIGH BAY DIAMOND SHAPE LAMP FIXTURE



1. Vacuum coated inner surface aluminum hood and clear glass cover maximize lumen output
2. Tempered glass cover held by profiled aluminum ring for better appearance and durable use
3. Diamond-shaped reflector optimize light uniformity
4. Special thermal design for longer lifespan
5. IP Class: IP65 (If use 3/4" hanging pole with ribbons), IP53 (If use hook)

LAMP AND BALLAST

1. Impact's 100-250W round type induction lamp with high lumen efficiency, high lumen maintenance, long lifespan and excellent CRI
2. Impact's 100-250W electronic ballast with die cast aluminum case features high power factor (>0.96), low energy loss and long lifespan

APPLICATION

Industrial factory, warehouse, stadium, airport, railway station, gas station, supermarket and other indoor locations

SPECIFICATIONS

lamp	wattage (w)	ballast loss(w)	voltage (v)	cct (k)	ambient temperature	installation	replace mh lamp(w)
WJY100H850W/T	100	<10					175
WJY120H850W/T	120	<12					250
WJY150H850W/T	150	<15	AC:120-277V AC:208-347V	5000	-25-40 °C -13-104 °F	Hook or 3/4" hanging pole	320
WJY200H850W/T	200	<20					400
WJY250H850W/T	250	<25					400

ORDER INFORMATION

MODEL ILI-DS	WATTS	COLOR TEMP	VOLTAGE	BASE	QUANTITY
Impact Lighting Inc.	100	5000	120 - 277V	Hook	
Diamond Shape	120		208 - 347V	0.75" Hanging Pole	
	150				
	200				
	250				