

INDUCTION BULB TYPE RETROFIT KIT W/ FLUSH MOUNT REMOTE BALLAST

APPLICATION, FEATURES AND BENEFITS

- Ideal replacement lamp for outlawed mercury lamps in outdoor acorns with Medium (E26) or Mogul (E40) base
- Bright White light (5000 K) for greater visibility and safety
- High Quality - Glare Free light with CRI above 83
- Electronic Ballasts made with long life components
- InstantON(TM) flicker-free Cold Start and Hot Re-Start
- High Power Factor, Low THD Ballast technology
- Advanced phosphors for high Lumen Maintenance and high lumen output
- Optional : 4100 K, 6500 K
- Universal Mounting Positions: Base up, Base down, Horizontal
- Made with Amalgam Technology



120

- New! Patented Technology



SPECIFICATIONS:

- Ballast Type: Electronic
- Start Method: InstantON
- Hot Re-start: InstantON
- Universal Input Line Voltage: 120-277 VAC
- Input Line Frequency: 50/60 Hz
- Lamp/Ballast System Life: 100,000 Hrs.
- Lumen Maintenance @75,000Hrs: >70%
- Color Temperature: 5000
- Color Rendering Index (CRI): above 83
- Minimum Starting Temperature: -20 F
- Maximum Operating Temperature: 160 F
- Lamp Operating Frequency: 250 kHz
- Power Factor: > 0.98
- Total Harmonic Distortion: < 10%
- Inrush Current Peak: < 10 Amp
- ETL Listed: Yes
- FCC Compliance: Part 18, Subp. C

PRODUCT INFORMATION - RETROFIT KIT



Item No.	Description	Watts	Initial Lumens	CRI	MOL (Oval)	MOL (Pear)	D (Oval)	D (Pear)
IL- 26080RK-UNV-FM	80W Induction BULB + Ballast Retrofit Kit	80	5,600	< 83	8.5 in. 222 mm	N/A	5.0 in. 127 mm	N/A
IL- 26100RK-M-UNV-FM	100W MINI Induction BULB + Ballast Retrofit Kit	100	7,000	< 83	8.5 in. 222 mm	N/A	5.0 in. 127 mm	N/A
IL / A - 26100RK-UNV-FM	100W Induction BULB + Ballast Retrofit Kit	100	7,000	< 83	9.25 in. 233 mm	8.25 in. 211 mm	5.0 in. 127 mm	6.0 in. 140 mm
IL / A - 26125RK-UNV-FM	125W Induction BULB + Ballast Retrofit Kit	125	8,750	< 83	9.75 in. 247 mm	9.25 in. 233 mm	5.25 in. 127 mm	6.0 in. 140 mm
IL / A - 26150RK-UNV-FM	155W Induction BULB + Ballast Retrofit Kit	150	10,500	< 83	9.75 in. 247 mm	9.25 in. 233 mm	5.25 in. 133 mm	6.0 in. 140 mm
IL / A - 26165RK-UNV-FM	165W Induction BULB + Ballast Retrofit Kit	165	11,550	< 83	9.75 in. 247 mm	9.25 in. 233 mm	5.25 in. 133 mm	6.0 in. 140 mm

UNV = 120-277 VAC

Note : Ballasts are included in the Retrofit Kits

PRODUCT INFORMATION - BALLASTS

Item No.	Description	Watts	Line Voltage Supply	THD	Power Factor	Ballast Dimensions	Mounting Dimensions
ILI-B-***W-UNV	Bulb Type Induction Ballast	80, 100, 125, 150, 165	120 - 277VAC	< 10%	0.98	8.0L x 3.0W x 2.0H in. 203 x 76 x 50 mm	9.0 in. 228 mm

*** Wattage : Must match bulb wattage