

ARCHITECTURAL SMART STARS DIGITAL LIGHTING SYSTEM™

SMART STARS DIGITAL LIGHTING SYSTEM™

- Easy Installation
- Industry Standard Connectors
- Save Time & Money
- Modular Design for Maximum Flexibility
 - Minimum SKU's for single inventory management
- Brighter than any other industry point lighting systems
- Total digital lighting system
 - Solid state element



178

- Total digital lighting system
 - Solid state element
- LED (Light Emitting Diode) Technology
- Full color, programmable control
- Application: Furniture, floor, ceiling and walls, restaurants, nightclubs and any exterior or interior lighting



SPECIFICATIONS



12 VOLT CONTROLLER

Part No.: DLS-C12 (Low Voltage)
 Voltage Input: 12 VAC
 Voltage Output: 12 VAC
 AMPS: 0.3
 WATTS: 135mA at 100%
 100mA at 75%
 80mA at 50%
 75mA at 25%
 Dimensions: 156.8mm X 91.75mm X 137.32mm
 Noise Level: 50db
 Operating Temperature: 0°C to 70°, -32°F to 158°F

120/220 VOLT CONTROLLER

Part No.: DLS-C120, DLS-C220
 Voltage Input: 1 20 VAC, 220 VAC
 Voltage Output: 12 VAC
 AMPS: 0.3
 WATTS: 135mA at 100%
 100mA at 75%
 80mA at 50%
 75mA at 25%
 Dimensions: 186.5mm X 91.75mm X 137.32mm
 Noise Level: 50db
 Operating Temperature: 0°C to 70°, -32°F to 158°F



LED LAMP

Part No.: DLS-L12
 Source: 12 Variable Intensity RGB LEDs
 Power Requirement: 220mA
 Power Consumption: 2.5W @ 12 VAC
 Dimensions: 51mm dia.
 Operating Temperature: 0°C to 70°C (32°F to 158°F)

LED LAMP

Part No.: DLS-L24
 Source: 12 Variable Intensity RGB LEDs
 Power Requirement: 440mA
 Power Consumption: 2.5W @ 12 VAC
 Dimensions: 51mm dia.
 Operating Temperature: 0°C to 70°C (32°F to 158°F)



LED LAMP ADAPTER

Part No.: DLS-LADAP
 Description: Light Adapter (L12 & L24) for Light
 Housing
 Dimensions: 1.5" (height) X 1-1/8" (dia.)



LED LAMP ADAPTER

Part No.: DLS-P1
 Dimensions: 186.5mm X 91.75mm X 137.32mm
 Mech. Properties: Tensile - 6800 psi Flex - 1700 MPA
 Impact: 840 in - lbs Thermal Conductivity: 0.23
 W/m - C
 Optical Properties: Light transmission - 88%



LED LAMP HOUSING

Part No.: DLS-L-HS
 Description: 5" Light Housing
 Dimensions: 5" (lens dia.) X 3-3/4" (hole dia.)

SMALL LED LAMP HOUSING

Part No.: DLS-L-HS-SM
 Description: 3-1/8" Light Housing
 Dimensions: 3-1/8" (lens dia.) X 2-1/2" (hole dia.)



LIGHT POINTS

Part No.: DLS-P2
 Star Point complete assembly without the plastic star point
 Voltage Input: 12VAC
 wattage: 80 mA at 100%
 50 mA at 75%
 30 mA at 50%
 15 mA at 25%

LIGHT POINTS

Part No.: DLS-P3
 Star Point complete assembly
 Voltage Input: 12VAC
 wattage: 80 mA at 100%
 50 mA at 75%
 30 mA at 50%
 15 mA at 25%