

LED THINGLOW™ SERIES




THINGLOW™ ULTRA BRIGHT - 110V

ThinGlow™ Ultra 110V is an indoor/outdoor flexible light strip that is an economical alternative to neon. Made with ultra bright SMD LED chips encased in a durable PVC flexible extrusion, ThinGlow™ Ultra 110V provides a clean neon look at fraction of the price and 1/10th the energy consumption. ThinGlow™ Ultra 110V is fully field cuttable making very simple to install. A variety of mounting accessories and power supplies further enhance ease of installation. Low energy consumption make ThinGlow™ Ultra 110V a very practical product. There are 220V, 120V, 24V and 12V ThinGlow™ Ultra features stunning color effect as it is fully color changeable. By employ specialized controller, it can produce over 1.6 million color grades. It is a very efficient and multi-purpose solution for various architectural in- and outdoor applications.


APPLICATIONS

Outdoor and indoor step lighting Construction decorative lighting Archway, cove lighting, canopy and bridge edge lighting Amusement park, theater and aircraft cabin mood lighting Emergency hallway lighting Pools and spas - underwater applications.



124

MODEL	COLOR TEMP	LENGTH	POWER CORD	JUMPER LENGTH	CHANNEL	VOLTAGE
IL-TGU or IL-HTGU						
Impact Lighting Inc.	WW- Warm White	2'	2"	003-SILVER	12V	
ThinGlow Ultra	CW - Cool White	4'	4"	003-WHITE	24V	
Bright 110V	R - Red	8'	8"	003-TRANSPARENT	120V	
	B - Blue	10'	12"	004-SILVER	220V	
	G - Green	Custom	Custom	004-WHITE		
	AM - Amber					
	RGB - Color Changing					



BENEFITS

- Flexible linear lighting
- Very bright SMD LEDs
- Low energy consumption and high light yield
- Protected against humidity: IP68
- Available in single colours &RGB
- Field cuttable
- Inter-connectable
- No maintenance and durable
- Minimal heat generation
- Long extension leads
- Possibilities to shorten, connect and roll
- Extremely functional and multi-purpose
- Accessories included
- Easy to install

SPECIFICATIONS

ITEM NO.	VOLTAGE	COLOR	DIMENSION	LED QTY/M	POWER (W/M)	LUMINOUS (LM/M)	ANGLE (DEGREE)	CUTTING LENGTH
IL-TGU-3528-40	110/220V	R,G,B,Y,CW,WW Pink	10X7MM	40pcs	3W	200	120	39.37"
IL-TGU-3528-60	110/220V	R,G,B,Y,CW,WW Pink	10X7MM	60pcs	5W	300	120	39.37"
IL-HTGU-5050-40	110/220V	R,G,B,Y,CW,WW W	12X8MM	40pcs	8W	560	120	39.37"
IL-HTGU-5050-60	110/220V	R,G,B,Y,CW,WW W	12X8MM	60pcs	12W	840	120	39.37"
IL-HTGU-5050-60-RGB	110/220V	RGB	12X8MM	60pcs	12W	500	120	39.37"
IL-TGU-3528-24	110/220V	R,G,B,Y,CW,WW Pink	10X7MM	60pcs	5W	300	120	24.2"
IL-HTGU-5050-24	110/220V	R,G,B,Y,CW,WW W	12X8MM	60pcs	12W	840	120	24.2"

* Power supplies are depended on length of run or quantity of fixtures for area.